

SPECIFICATIONS for TUBE- TECH CL 1B

Impedance

Input:	600 Ohm
Output	<60 Ohm

Frequency response @ -3dB 5 Hz to 25 kHz

Distortion THD+N @ 40Hz

	0 dBU	0,15 %
	+10 dBU	0,15 %
Max. output:	+26 dBU	<1 %
Max. input:	+21 dBU	<1 %

Noise Rg=200 Ohm

Output Gain @	0 dB	+30 dB
22 Hz-22 kHz	< -85 dBU	< -75 dBU
CCIR-468-4	< -75 dBU	< -65 dBU

Cross talk @ 10 kHz: < - 60 dB

CMMR @ 10 kHz < - 60 dB

Gain off to +30 dB

Compressor

Ratio:	2:1 to 10:1
Threshold	off to -40 dBU
Attack	0,5 ms to 300 ms
Release:	50 ms to 10 s

Tubes

ECC 82	1 pc
ECC 83	1 pc

Dimensions

Height: 3 units	132 mm	5,2"
Width:	483 mm	19,0"
Depth:	170 mm	6,7"

Weight

Net:	4,1 kg	9,0 lbs
Shipping:	5,9 kg	13,0 lbs

Power requirements

@ 115 V/230 V, 50-60 Hz	22 W
-------------------------	------

Notes

All specifications @ RL = 600 Ohm
Lydkraft reserves the right to alter specifications without prior notice