

SPECIFICATIONS for TUBE- TECH MP 1A

Impedance

Input, Mic. Preamp:	> 1,2 kOhm
Input, DI:	> 1 MOhm/82pF
Output	<60 Ohm

Frequency response @ -3dB 5 Hz to 60 kHz

Distortion THD+N @ 40Hz

	0 dBU	0,20 %
	+10 dBU	0,20 %
Max. output:	+26 dBU	<1 %
Max. input:	+21 dBU	<1 %

Noise Rg=200 Ohm

Output Gain @	+20 dB	+60 dB
22 Hz-22 kHz	< -85 dBU	< -60 dBU
CCIR-468-4	< -75 dBU	< -50 dBU

CMMR @ 10 kHz < - 60 dB

Gain

Mic. Preamp	0 to 70 dB
DI	10 to 60 dB

Tubes

ECC 82	2 pc
ECC 83	4 pc

Dimensions

Height: 2 units	88 mm	3,5"
Width:	483 mm	19,0"
Depth:	165 mm	6,5"

Weight

Net:	4,3 kg	9,5 lbs
Shipping:	6,1 kg	13,4 lbs

Power requirements

@ 115 V/230 V, 50-60 Hz	30-45 W
-------------------------	---------

Notes

All specifications @ RL = 600 Ohm
Lydkraft reserves the right to alter specifications without prior notice