

Specifications for TUBE-TECH CL 2A

Impedance

Input:	5K ohm
Output:	<60 ohm

Frequency response @ -3 dB: 5 Hz to 40 kHz

Distortion THD+N @ 40 Hz

	0 dBU	< 0,15 %
	+10 dBU	< 0,15 %
Max. output:	+26 dBU	< 1 % THD
Max input PAD:	+21 dBU	< 1 % THD

Noise Rg=200 ohm

Gain:	0 dB	+10 dB
22Hz-22kHz:	< -80 dBU	< -80 dBU
CCIR-468-4:	< -70 dBU	< -70 dBU

CMRR @ 10 kHz: < -60 dB

Gain: Off to +10dB

Compressor

Ratio;	1,5:1 to 10:1
Threshold:	off to -20dBU
Attack:	3 ms to 60ms
Release:	60 ms to 2 s

Tubes

ECC 82	2 pcs.
ECC 83	2 pcs.

Dimensions

Height: 2 units	88 mm	3,5"
Width:	483 mm	19,0"
Depth:	205 mm	8,1"

Weight

Net:	5,8 kg	12,8 lbs.
Shipping:	7,1 kg	15,6 lbs.

Power requirements:

@ 115V/230V	30-45W
-------------	--------

Notes

All specifications @ RL=600 ohm
Lydkraft reserves the right to alter specifications without prior notice