

SPECIFICATIONS for TUBE- TECH SSA 2B

Impedance

Input:	50 kOhm
Output	<60 Ohm

Frequency response @ -3dB 5 Hz to 100 kHz

Distortion THD+N @ 40Hz

	0 dBU	0,05 %
	+10 dBU	0,05 %
Max. output:	+26 dBU	<1 %
Max. input:	+30 dBU	<1 %

Noise Rg=200 Ohm

Output Gain @	0 dB		+10 dB	
Input used	1	10	1	10
22 Hz-22 kHz	< -90	< -85	< -80	< -75 dBU
CCIR-468-4	< -80	< -75	< -70	< -65 dBU

CMMR @ 10 kHz < - 60 dB

Gain

0,5 dB steps	+/- 0-3 dB
1 dB steps	+/- 3-6 dB
2 steps	+/- 6-10 dB

Gain tracking

Between channels < 0,1 dB

Cross talk @ 10kHz < - 70 dB

Tubes

ECC 82	2 pc
ECC 83	2 pc
ECC 88	4 pc

Dimensions

Height: 2 units	88 mm	3,5"
Width:	483 mm	19,0"
Depth:	205 mm	8,1"

Weight

Net:	5,4 kg	11,8 lbs
Shipping:	6,5 kg	14,3 lbs

Power requirements

@ 115 V/230 V, 50-60 Hz	40-55 W
-------------------------	---------

Notes

All specifications @ RL = 600 Ohm
Lydkraft reserves the right to alter specifications without prior notice