

Specifications for TUBE-TECH Mic-preamplifier MP 2A

Impedance

Mic Input:	600/1200/2400 ohm
DI input:	>1 Mohm/82 pF
Output:	<60 ohm

Frequency response @ -3 dB: 5 Hz to 60 kHz

Distortion THD+N @ 40 Hz

	0 dBU	< 0,10 %
	+10 dBU	< 0,10 %
Max. output:	+26 dBU	< 1 % THD
Max input without PAD:	+6 dBU	< 1 % THD
Max input with PAD:	+26 dBU	< 1 % THD

Noise Rg=200 ohm

Gain:	+20 dB	+60 dB
22Hz-22kHz:	< -82 dBU	< -60 dBU
CCIR-468-4:	< -72 dBU	< -50 dBU

CMRR @ 10 kHz: < -60 dB

Gain:

Mic Input:	-10 +70 dB
DI input:	0 to 60 dB

Tubes

ECC 82	2 pcs.
ECC 83	4 pcs.

Dimensions

Height: 2 units	88 mm	3,5"
Width:	483 mm	19,0"
Depth:	165 mm	6,5"

Weight

Net:	4,3 kg	9,5 lbs.
Shipping:	6,1 kg	13,4 lbs.

Power requirements:

@ 115V/230V	30-45W
-------------	--------

Notes

All specifications @ RL=600 ohm
Lydkraft reserves the right to alter specifications without prior notice