

SPECIFICATIONS for TUBE- TECH CL 1B

Impedance

| | |
|--------|---------|
| Input: | 600 Ohm |
| Output | <60 Ohm |

Frequency response @ -3dB 5 Hz to 25 Hz

Distortion THD+N @ 40Hz

| | | |
|--------------|---------|--------|
| | 0 dBU | 0,15 % |
| | +10 dBU | 0,15 % |
| Max. output: | +26 dBU | <1 % |
| Max. input: | +21 dBU | <1 % |

Noise Rg=200 Ohm

| Output Gain @ | 0 dB | +30 dB |
|---------------|-----------|-----------|
| 22 Hz-22 kHz | < -85 dBU | < -75 dBU |
| CCIR-468-4 | < -75 dBU | < -65 dBU |

Cross talk @ 10 kHz: < - 60 dB

CMMR @ 10 kHz < - 60 dB

Gain off to +30 dB

Compressor

| | |
|-----------|------------------|
| Ratio: | 2:1 to 10:1 |
| Threshold | off to -40 dBU |
| Attack | 0,5 ms to 300 ms |
| Release: | 50 ms to 10 s |

Tubes

| | |
|--------|------|
| ECC 82 | 1 pc |
| ECC 83 | 1 pc |

Dimensions

| | | |
|-----------------|--------|-------|
| Height: 2 units | 132 mm | 5,2" |
| Width: | 483 mm | 19,0" |
| Depth: | 170 mm | 6,7" |

Weight

| | | |
|-----------|--------|----------|
| Net: | 4,1 kg | 9,0 lbs |
| Shipping: | 5,9 kg | 13,0 lbs |

Power requirements

| | |
|-------------------------|------|
| @ 115 V/230 V, 50-60 Hz | 22 W |
|-------------------------|------|

Notes

| |
|--|
| All specifications @ RL = 600 Ohm |
| Lydkraft reserves the right to alter specifications without prior notice |